

(317) 627-4894		
BASIC QUOTE INFO:		Length Around Finished
Enter Project Name:		Web Width
1) Size of label: width across web X (see illustration in upper corner of this sheet- width across	length around web_ coss always listed 1st x length a	round 2 <sup>nd</sup> )
2) Surface applied to: (see attachment on plastic resin types or advise other states.	urface: corrugated, metal type	, glass, etc.)
3) Conditions of labeling environment if not dry, cle (very important to know about freezing, chilling, or high	ean, and ambient temp:  h heat temp ranges; condensat	ion; or any fluids or contaminants)
4) Label material:  (choice of white gloss paper   direct thermal paper   the metallic film   other)	ermal transfer paper   metallic	paper   white film   clear film
5) Choose permanent, repositionable or removable a	adhesive:	
<ul> <li>6) # of ink colors: (please attach or include</li> <li>7) Protective or gloss coating or laminating: (choice of none   gloss varnish   matte varnish   textured varn</li> </ul>		
<ul> <li>8) Maximum outside diameter of roll:</li></ul>	" to avoid curl—some portable the	ermal printers require 1")
10) Unwind position: (see unwind chart attached #1 thru #4 are 99+% most com	mon)	
11) Total quantity per order:		
Total quantity to be inventoried:	Total quantity per year:	
12) Applying by hand or auto-applicator:	Make:	Model:
13) Payment terms desired:	(debit card, credit card or	Net 30 days are standard)
If using a desk-top printer or print-and- Direct thermal, thermal transfer, or ink- (direct thermal uses no ribbons, thermal transfer	jet?	
Make: Model		
Special box, case, or pallet pack-outs or dimensions:		
Special color approvals such as GMI or Delta E:		
Agency compliance such as UL, CSA, AIB, SQF, FDA	A, ISO, or CE:	
Special paperwork such as First Article, PPAP, Certific	cates of Conformance or An	alysis:

Anything else we should know?

Corner Radius (.125" is standard)

↓Gap

Maximum Outside Diameter of Roll

Core Size